

LINEAR EDGEBANDER



DESCRIPTION

The T-EB-155 is one of the professional series of edgebanders manufactured by Turanlar. The T-EB-155 performs perfectly with its PLC Touch Screen, Pre-Milling, Top and Bottom Trimming units, Radius Scraping and Buffing processes as well as our standard Teflon coated EVA Hotmelt glue pot system found on the majority of the Turanlar UK Edgebander range. It can apply all common edging materials between 0.4-3mm (PVC, Veneer, ABS, Melamine & Solid Wood etc.) all up to 50mm wide panels. It has a feeding speed of 15m/min. The T-EB-155 has corner rounding capabilities with the trimming units provided on the machine. The machine is manufactured to the highest European standards expected within the UK market. There is also the option of having a separate PUR Glue system with this machine at an extra cost. Please get in touch if you require more details and pricing.





T-EB-155 - SPECIFICATION SHEET

TURANLARUK

PRODUCT SPECIFICATION

Electrical Level:	415 V
Phase:	Three Phase
Nominal Current:	17A
Edge Material Thickness:	0.4 – 3mm
Board Thickness:	
Without Pre-Milling	10-50mm
With Pre-Milling	10-46mm
Speed:	15m/min
Total Electrical Power:	9 kW
Total Air Pressure:	6 Bar
Total Air Usage:	300lt/min
Working Height:	910mm
Pre-Milling:	2 x 1,50kW/ 12000rpm
End Cutting:	2 x 0,37kW / 12000rpm
Trimming:	2 x 0,37kW/ 12000rpm
Trimmer Motor:	0,37kW/12000rpm
Buffing Motor:	2 x 0,18kW/1400rpm
Dust Extraction Diameter:	150mm
Machine Dimensions (WxLxH):	1010x5300x1700mm
Machine Weight:	2300kg



T-EB-155 - SPECIFICATION SHEET

TURANLARUK

TECHNICAL DIMENSIONS





