

LINEAR EDGEBANDER

TURANLAR UK



DESCRIPTION

The T-EB-156 is one of the professional series of edgebanders manufactured by Turanlar. The T-EB-156 performs perfectly with its standard units i.e. PLC Touch Screen, Pre-Milling, Top and Bottom Trimming units, Radius Scraping and Buffing processes as well as our Teflon coated EVA Hotmelt glue pot system found on the majority of the Turanlar UK Edgebander range. It can apply all common edging materials between 0.4-3mm (PVC, Veneer, ABS, Melamine & Solid Wood etc.) all up to 50mm wide panels. It has a feeding speed of 15m/min.

The T-EB-156 is one of the most popular models of Turanlar Edgebanding machinery with most manufacturers due to its specification and cost. With its pre-milling knives before the edge is applied to the panel as well as contour top and bottom trimming units in order to give a perfect corner rounding finish on the panel. Ideal for manufacturers who are completing postformed work due to the flexibility of the trimming units which can trim and contour. Its modern, functional & strong design is from over five decades worth of experience manufacturing Edgebanding machinery. There is also the option of having a separate PUR Glue system with this machine. Please get in touch if you require more details and pricing.





PRODUCT SPECIFICATION

Electrical Level:	415 V
Phase:	Three Phase
Nominal Current:	20A
Edge Material Thickness:	0.4 – 3mm
Board Thickness:	
Without Pre-Milling	10-50mm
With Pre-Milling	10-46mm
Speed:	15m/min
Total Electrical Power:	10 kW
Total Air Pressure:	6 Bar
Total Air Usage:	300lt/min
Working Height:	910mm
Pre-Milling:	2 x 1,50kW/ 12000rpm
Trimming:	4 x 0,37kW/ 12000rpm
Buffing Motor:	2 x 0,18kW/1400rpm
Dust Extraction Diameter:	150mm
Machine Dimensions (WxLxH):	1010x5300x1700mm
Machine Weight:	2350kg

TECHNICAL DIMENSIONS

