

THROUGHFEED SOFTFORMER

TURANLAR UK

DESCRIPTION

The T-SF-161 throughfeed softforming machine is a single-side track fed machine. It is an ideal solution for standard soft edge application and soft door edging. The T-SF-161 does not apply glue itself; the operators must use a pre-glued tape that is activated by the heating unit on the machine. This size throughfeed softformer is ideal for SME businesses which have a requirement for softforming but do not have the requirement for full production.



PRODUCT INFORMATION

The T-SF-161 comes with some standard features that you can find in our range of Turanlar UK Throughfeed postformers i.e. Carousel Station (3 Different Cartridges) speed adjustment and automated track feed system. In addition the components that make this machine a softformer include the following:

- Top and Bottom Trimming Units
- Suitable for "L" profiled panel/door edges
- Band Feed Table
- Grooving Saw and Top and Bottom Buffing Unit
- Hot Air Heaters

PRODUCT SPECIFICATION

Electrical Level:	415V
Nominal Current:	15 A
Banding Material Thickness:	0.4-1 mm
Banding Material Height:	60 mm
Speed:	6, 5 m/min
Total Electrical Power:	8 kW
Working Height:	870 mm
Total Air Pressure:	6 Bar
Trimmer Motor:	2x 0,37 kW 12000 rpm
Buffing Motor:	0,18 kW
Hot Air Blower:	2 x 2600w
Total Air Usage:	15lt/min
Dust Extraction Entrance:	Ø 150 mm
Machine Width:	920 mm
Machine Length:	4000 mm
Machine Height:	1600mm
Machine Weight:	1700kg

TECHNICAL DIMENSIONS

